

southco®

PROPRIETARY ITEM - EXCEPT FOR USES EXPRESSLY GRANTED IN WRITING INFORMATION DISCLOSED HEREON IS CONFIDENTIAL AND ALL RIGHTS PATENT AND OTHERWISE ARE RESERVED BY SOUTHCO, INC.

REV	DATE	DRAWN/CHKD	DESCRIPTION
C	09APR2002	GDM	UPDATE FORMAT

N O . 1 0 L I N E R R I V E T

DATE	28AUG81
------	---------

DRAWN	SJM
-------	-----

CHKD	
------	--

SCALE	NTS
-------	-----

DRAWING NUMBER	TD-10-J
----------------	---------



THIRD ANGLE PROJECTION

A PAPER SIZE

SOUTHCO PERFORMANCE GUIDELINES
 THE PERFORMANCE GUIDELINES SHOWN ON THIS PAGE ARE SUPPLIED AS A GENERAL GUIDE ONLY, AS CONDITIONS VARY WITH EACH APPLICATION AND METHOD OF INSTALLATION. STRENGTH DATA GIVEN IS FOR FAILURE OF THE PRODUCT OR FOR SUFFICIENT DEFORMATION TO MAKE PRODUCT INOPERABLE. NO SAFETY FACTOR HAS BEEN APPLIED IT IS RECOMMENDED THAT THE USER REQUEST A PRODUCT SAMPLE FOR TESTING TO DETERMINE THE SUITABILITY OF THE PRODUCT FOR THE PURPOSE INTENDED AND USER'S PARTICULAR APPLICATION.

PART NUMBER 10-13-706-13 WAS TESTED USING TWO .156 THICK HARDENED STEEL TEST PLATES AT NOMINAL GRIP.

ULTIMATE TENSILE - 3000 N / 675 LBS
 ULTIMATE SHEAR - 4220 N / 950 LBS